

BENEFITS

- Laser engraving and cutting
- Glossy or frosted finish
- Excellent for clear signage
- Laser and rotary engravable
- Interior and exterior use



APPLICATIONS

Interior and exterior signage applications

SPECIFICATIONS

Finish	Glossy
Composition	Acrylic
Engraving depth	0.25 mm (0.010")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	0.5 mm (0.020")
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	-
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (180°F)

TECH TIPS

Acrylic sheets can be engraved, paint filled, or used for cutouts. Another common use is to simply add thickness to an engraved sheet of metal or plastic. The added thickness has a strong presence on the wall - especially helpful if the sign is not framed.

Opaque

white	83440	83441	3.2 mm (1/8")	6 mm (.20")
opaque black	83442	83443	3.2 mm (1/8")	6 mm (.20")

Frosted

frosted white	83431	3.2 mm (1/8")
frosted light blue	83434	3.2 mm (1/8")
frosted sky blue	83438	3.2 mm (1/8")
frosted blue ocean	83435	3.2 mm (1/8")
frosted blue lagoon	83437	3.2 mm (1/8")
frosted green	83436	3.2 mm (1/8")
frosted yellow	83432	3.2 mm (1/8")
frosted pink	83439	3.2 mm (1/8")
frosted mauve	83433	3.2 mm (1/8")

Clear

clear	83423	83424	83425	3.2 mm (1/8")	6 mm (.20")	10 mm (.40")
translucent green	34096	34098		3.2 mm (1/8")	6 mm (.20")	
translucent blue	33971	33972		3.2 mm (1/8")	6 mm (.20")	

Fluorescent

yellow	83428	3.2 mm (1/8")
orange	83430	3.2 mm (1/8")
pink	83429	3.2 mm (1/8")



WATCH VIDEO HERE



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

