

BENEFITS

- Phenolic material
- Low glare
- Resistant to chemicals and solvents
- Non-flammable
- Conforms to military specifications
ASTM D 709 ES-1, ES-2, ES-3
- Electrically non-conductive

APPLICATIONS

Industrial identification...

SPECIFICATIONS

Finish	Low Glare
Composition	Rigid Thermoset Material, 3-ply
Engraving Depth	.012"
Full Sheet	36" x 39"
Half Sheet	18" x 39" (add -H)
Quarter Sheet	18" x 19.5" (add -Q)
Other Size(s)	-


CAPABILITIES

Interior	■
Exterior	-
Shear	-
Saw	■
Screen Print	■
Hot Stamp	■
Heat bending	-
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	-
Min. temp.	-40°C (-40°F)
Max. temp.	180°C (365°F)

TECH TIPS

Thanks to its specific characteristics, this material is the ideal choice for all your industrial identification needs.

Gravostrat™ can be laser engraved but not laser cut.



Low Glare

Surface / Core Colour / Surface

White / Black / White	80194 (1/16")* 80195 (1/8")*
-----------------------------	---

Yellow / Black / Yellow	80191 (1/16")* 80196 (1/8")*
-------------------------------	---

* Double Sided, 3 Ply

Gravostrat™ can be laser engraved but not laser cut.

Gravostrat™ may be subject to slight variations in thickness.

Low Glare

Surface / Core Colour / Surface

Red / White / Red	80193 (1/16")* 80198 (1/8")*
-------------------------	---

Black / White / Black	80192 (1/16")* 80197 (1/8")*
-----------------------------	---

